

MT-LVL E9

ROOF BATTENS & GENERAL FRAMING



GRADE: E9
SIZES: 70x35
LENGTHS: 6.0m
TOLERANCE: +/-2mm
TREATMENT: H2-S to AS/NZS1604.4

- ◉ **STRAIGHT, LONG LENGTHS**
- ◉ **PREDICTABLE PERFORMANCE**
- ◉ **H2-S PROTECTED AGAINST TERMITES**

MT-LVL E9 is available as a 70x35 6.0m length specifically designed for use as roof battens as well as general framing applications. Roof battens using MT-LVL E9 will be straighter, less prone to breaking, and have reduced tendency to split at connections.

For general framing applications, MT-LVL E9 has higher strengths than F8 and a comparable stiffness. It can be substituted where F8 is specified or designed using F8 span tables/software, making both design and certification simple. The inclusion of a glueline protection against termites provides added security.

MT-LVL E9 ROOF BATTEN SPAN TABLE (70x35 MT-LVL E9 on flat)

Wind Classification	Max Truss/Rafter Spacing (mm)	Max Roof Batten Spacing (mm) <i>General & within 1.2m of edge</i>	Max Roof Batten Spacing (mm) <i>General & within 1.2m of eaves corner</i>
N1, N2, N3	1000	950	950
N4	950	950	700

NOTES:

1. Roof battens designed for sheet roof only (<25kg/m²). 2. Roof battens to be continuous over minimum 2 spans. 3. MT-LVL E9 has not been approved for use in roof trusses and floor trusses.

Meyer
TIMBER

Meyer
TIMBER
Victoria

Meyer
TIMBER
New South Wales

Meyer
TIMBER
Queensland

Meyer
TIMBER
Tasmania

www.meyertimber.com.au

AVAILABLE THROUGH:

