

WARRANTY AND INSTALLATION

DISPOSAL OF WASTE AND OFFCUTS

Do not burn off cuts or sawdust from any preservative treated timber. Such offcuts and sawdust should be disposed of by approved local authority methods.

WARRANTY

To maintain the limited guarantee offered by preservative suppliers, details pertaining to the products used on the project must be kept. For example: end tags and proof of purchase. meyBASE4 preservative guarantees require every cut, rebate or hole to have a preservative sealer applied and re-primed with a quality primer. This limited guarantee covers the use of meyBASE4 products against fungal decay, termite attack and insect borers only.

PRIOR TO INSTALLATION

Ensure that all dirt, dust or any contaminants are cleaned from the surface of the board.

- Any bare timber areas exposed through cutting or notching must be retreated with an approved treatment re-sealer prior to priming with a quality primer.
- meyBASE4 products are generally supplied to the site with a moisture content of approximately 12% {+/- 2%}. At the time of installation, the meyBASE4 product must have a moisture content close to the local expected average moisture content. For sites where the moisture content is significantly different, some acclimatisation will be required prior to installation.
- meyBASE4 primer only forms part of the final painting system, it is not weatherproof paint. Do not leave exposed to weather for an extended period.

JOINT SEALING

All joints irrespective of the finish should be re-sealed, including stopped ends, with a mastic or silicone sealant that is compatible with the intended paint finish. The sealant should be placed onto the ends of the boards before pushing the ends together. Any excess sealant should be removed from the faces of the boards as soon as the boards are fixed.

TOPCOATS

It is recommended that if the product is being used as an exposed beam, at least two topcoats of premium paint be applied in accordance with the paint manufacturer's recommendations after fixing. The minimum paint film requirements can be found on the tin.



Scan the QR code for
product information.

MEYERTIMBER.COM.AU